Ref. 5

PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2006-080116

(43) Date of publication of application: 23.03.2006

(51)Int.Cl.

H01L 43/08 (2006. 01) G11B 5/39 (2006. 01) (2006.01) 43/10 *HO1L* (2006.01) HOIL 43/12 H01L 27/105 (2006. 01) 21/8246 (2006. 01) H01L

(21)Application number : 2004-259280

(71)Applicant: CANON ANELVA CORP

NATIONAL INSTITUTE OF **ADVANCED INDUSTRIAL &**

TECHNOLOGY

(22)Date of filing:

07.09.2004


(72)Inventor:

DAVID DJAYAPRAWIRA

TSUNEKAWA KOJI **NAGAI MOTOMASA** MAEHARA DAIKI YAMAGATA SHINJI WATANABE NAOKI YUASA SHINJI

(54) MAGNETORESISTIVE EFFECT ELEMENT AND ITS MANUFACTURING METHOD (57) Abstract:

PROBLEM TO BE SOLVED: To provide a magnetoresistive effect element which is superior in MR ratio and of which mass-productivity and practicality are improved, and to provide its manufacturing method. SOLUTION: The magnetoresistive effect element (TMR element 10) has a lamination structure (TMR element 12) which is formed of a pair of ferromagnetic layers and a barrier layer located at the middle position between them. At least one ferromagnetic layer is provided with such a portion in contact with the barrier layer that has an amorphous state, and the barrier layer is an MgO layer with a single crystal structure.



LEGAL STATUS

[Date of request for examination]

24.08.2007

[Date of sending the examiner's decision of

rejection]

[Kind of final disposal of application other than

the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]